

Index

- /etc/lwresd.conf, 71
- /etc/named.conf, 25
- /etc/rndc.conf, 18, 22
- /var/run/named.pid, 99
- \$GENERATE directive, 155
- \$INCLUDE directive, 28, 65, 154
- \$ORIGIN directive, 153, 154
- \$TTL directive, 152, 154, 176
- 53 (port), 16, 32, 43, 54, 73, 101, 112, 138, 140, 167
- 953 (port), 18, 23, 84
- A record, 69, 147, 153
- A6, 111
- A6 record, 68, 69, 148, 180
- AA, 2
- AAAA record, 68, 69, 147
- acache, 128
- acache-cleaning-interval option, 129
- acache-enable options, 129
- access control, 77, 109
 - allow-query, 80
- Access Control Lists, 83, 157
- ACL, 83, 157
- acl statement, 83
- additional section cache, *see* acache
- additional-from-auth option, 105
- additional-from-cache option, 105, 129
- address match list, 77, 83
 - any, 83
 - localhost, 83, 110
 - localnets, 83, 110
 - none, 83
- address prefix list record, 148
- AFS database servers record, 148
- AFSDB record, 148
- algorithm, 62
- alias record, 148
- allow-notify option, 109
- allow-query access control, 80
- allow-query option, 110
- allow-query-cache option, 110
- allow-query-cache-on option, 110
- allow-query-on option, 110
- allow-recursion option, 110
- allow-recursion-on option, 111
- allow-transfer option, 111
- allow-update option, 63, 111, 144, 169
- allow-update-forwarding option, 111
- allow-v6-synthesis option, 111
- also-notify option, 113, 140
- alt-transfer-source option, 115
- alt-transfer-source-v6 option, 116
- any (address match list), 83
- APL record, 148
- asterisk, 84
- auth-nxdomain option, 102
- authentic data (AD) bit, 44
- authoritative, 102, 138
- authoritative answer, 2
- authoritative name server, 2
- authoritative name server record, 148
- authoritative-only server, 80
- avoid-v4-udp-ports option, 116
- avoid-v6-udp-ports option, 116
- AXFR, 57
- BADKEY, 63
- BADSIG, 64
- BADTIME, 64
- bandwidth, 106
- base-64, 62
- binary format zone file, 156
- binary label, 68, 111
- BIND, 173

- BIND 4, 75, 115, 121, 131, 138, 173–176, 178
- BIND 8, 10, 17, 61, 66, 75, 85, 87, 98, 102–105, 108, 114–117, 127, 131, 138, 142, 156, 174, 175
- BIND 9, 174
- bitstring, 68, 180
- blackhole option, 111
- bogus networks, 157
- bogus option (server), 130
- built-in zones, 124
- cache file, 17
- cache-file option, 17, 98
- caching, 4
 - negative answers, 122
 - positive answers, 122
- caching server, 4
- caching-only name server, 80, 189
- canonical name record, 148
- carriage return, 105
- category (logging), 90
- CERT record, 148
- certificate record, 148
- channel statement (logging), 87
- channels, 87
- CHAOS, *see* Chaosnet
- Chaosnet, 124, 139, 149
- character set, 178
- check-integrity option, 107
- check-mx option, 107
- check-mx-cname option, 108
- check-names option, 107, 140, 179
- check-sibling option, 108
- check-srv-cname option, 108
- check-wildcard option, 107
- checking disabled (CD) bit, 45
- Checking Disabled (CD) flag, 92
- chroot, 16, 73, 168
- chrooted environment, 168
- class (zone), 139
- cleaning-interval option, 118
- client TCP connections, 118
- clients-per-query option, 123
- CNAME
 - multiple, 104
- CNAME record, 148
- comments, 78
- Computer Systems Research Group, 173
- configuration file, 15, 75
- control channels, 84
- controls statement, 22, 23, 84
 - inet, 84
 - unix, 84
- core dump, 117
- coresize option, 117
- cross compiling, 9
- cryptographic authentication, 65
- CSRG, 173
- cyclic, 129
- DARPA, 173
- database (zone), 141
- database drivers, 141
- database dump, 99
- datasize option, 117
- deallocate-on-exit option, 102
- Debian Linux, 12
- debug, 90
- debug level, 15, 88
- debugging, 21
- debugging level, 19
- default root servers, 139
- default_debug (logging), 90
- delegation, 3
- delegation path, 45
- delegation-only (zone type), 139
- delegation-only (zone), 141
- delegation-only logging, 92
- denial of service (DoS) attacks, 157
- denial of service attacks, 158, 167
- diagnostic tools, 41
- dialup option, 102
- Diffie-Hellman key, 64, 98
- dig
 - examples, 48
- dig command, 41
- digital certificate record, 148
- directive
 - \$GENERATE, 155
 - \$INCLUDE, 28, 65, 154

- \$ORIGIN, 153, 154
- \$TTL, 152, 154, 176
- directory option, 98
- disable-algorithms option, 101
- disable-empty-zone option, 127
- DLV, 36
- DLV record, 101
- DNAME record, 148
- DNS, 1
- DNS protocol, 2
- DNSKEY record, 148
- DNSSEC, 5, 10, 65, 106
- dnssec logging, 92
- DNSSEC security roots, 132
- DNSSEC signature data, 149
- dnssec-accept-expired option, 107
- DNSSEC-bis, 65
- dnssec-enable option, 106
- dnssec-keygen, 33, 35
- dnssec-keygen command, 61, 65
- dnssec-lookaside option, 101
- dnssec-makekeyset., 25
- dnssec-must-be-secure option, 102
- dnssec-signkey, 25
- dnssec-signzone, 35, 38
- dnssec-signzone command, 66
- dnssec-validation option, 107
- DNSSECbis signature data, 149
- DNSSEC ok (DO) flag, 92
- dollar sign, 177
- domain, 1, 2
- Domain Name System, 1
- domain names, 1
- DS record, 148
- DS records, 36
- dual-stack servers, 109
- dual-stack-servers option, 109
- dump, 56
- dump caches, 19
- dump-file option, 99
- dynamic DNS, 29
- dynamic DNS updates, 111
- dynamic update, 19, 55, 61, 169
- dynamic updates, 144
- EDNS flag, 92
- edns option (server), 131
- EDNS UDP buffer size, 123
- EDNS UDP message size, 123
- edns-disabled logging, 92
- edns-udp-size option, 123, 131
- EDNS0, 47, 178
- empty zones, 125, 126
- empty-contact option, 127
- empty-server option, 126
- empty-zones-enable option, 127
- errors, 175
- exclamation mark, 77
- fake-iquery option, 103
- fetch-glue option, 103
- file logging destination, 87
- files option, 117
- firewall, 4, 80, 167, 168
- flush-zones-on-shutdown option, 103
- FORMERR, 63, 92
- forward (zone type), 139
- forward option, 109, 141
- forwarder, 4
- forwarders option, 71, 109, 142
- forwarding, 4
- forwarding queries, 108
- frozen dynamic zone, 21
- full zone transfer, *see* AXFR
- global options, 97
- global position record, 148
- glue, 180
- glue resource records, 103
- GPOS record, 148
- GPS, 148
- GSS-TSIG, 144
- GSS-TSIG protocol, 98
- hardware, 5
- has-old-clients option, 103
- heartbeat-interval option, 102, 118
- Hesiod, 149
- hesiod class, 139
- HINFO record, 148
- hint (zone type), 139, 160
- hint zone, 21, 139

- history, 173
- host command, 49
- host info record, 148
- host-statistics option, 103
- host-statistics-max option, 117
- hostname option, 124
- idle timeout, 114
- IDN, 48, 51
- in-addr.arpa, 152
- include statement, 85
- incremental zone transfer, *see* IXFR
- inet control channel, 84
- interface-interval option, 118
- interfaces, 111
- internal cache, 128
- internal name servers, 6
- internationalized domain name, *see* IDN
- Internet class, 139
- Internet Drafts, 187
- Internet Systems Consortium, 171, 174
- inverse mapping, 152
- ip6.arpa, 68, 180
- ip6.int, 68, 180
- IPv6, 10, 15, 68, 69, 75, 180
 - reverse lookups, 68
- IQUERY, 103
- ISC, 171
- ISDN record, 148
- IXFR, 21, 56
- ixfr-base (zone), 142
- ixfr-from-differences option, 106
- ixfr-tmp-file zone option, 142
- Jeeves, 173
- jitter, 37
- journal, 56
- journal (zone), 142
- journal file, 19, 55
- Kerberos 5, 98
- key exchanger record, 148
- KEY record, 148
- key statement, 23, 86
- key-directory option, 98
- keys
 - generating, 65
- keys option (server), 131
- KSK, 38
- KSK flag, 108
- KX record, 148
- lame server, 92, 122
- lame-ttl option, 122
- lightweight resolver (lwres), 71, 72, 93
- line breaks, 177
- Linux, 16
- listen-on lwres option, 93
- listen-on option, 111
- listen-on-v6 option, 112
- load balancing, 153
- LOC record, 148
- localhost (address match list), 83, 110
- localnets (address match list), 83, 110
- log
 - size, 88
 - versions, 87
- logging, 73, 166
- logging queries, 107
- logging statement, 87, 176
 - channel, 87
- logging to stderr, 16
- lwres statement, 93
 - listen-on, 93
 - ndots, 93
 - search, 93
 - view, 93
- lwresd command, 71, 72
- mail exchange record, 148
- maintain-ixfr-base option, 103
- many-answers, *see* transfer-format option
- master, 152
- master (zone type), 138
- master file, 3, 26, 123, 153, 156, 161, 177
 - errors, 175
- master zones, multiple, 106
- masterfile-format option, 123
- masters statement (zone), 93

- match-clients (view), 133
- match-destinations (view), 133
- match-mapped-addresses option, 106
- match-recursive-only (view), 133
- max-acache-size option, 5, 129
- max-cache-size option, 5, 118
- max-cache-ttl option, 122
- max-clients-per-query option, 123
- max-ixfr-log-size option, 117
- max-journal-size option, 117
- max-ncache-ttl option, 122
- max-refresh-time option, 123
- max-retry-time option, 123
- max-transfer-idle-in option, 114
- max-transfer-idle-out option, 114
- max-transfer-time-in option, 114
- max-transfer-time-out option, 114
- max-udp-size option, 123, 131
- MD record, 180
- memory, 5
- memory leaks, 102
- memory usage, 16
- memory usage statistics, 16, 73
- memstatistics-file option, 99
- MF record, 180
- Microsoft Windows, 7, 115
- min-refresh-time option, 123
- min-retry-time option, 123
- min-roots option, 122
- minimal-responses option, 103
- mmencode command, 62
- Mockapetris, Paul, 173
- multi-master option, 106
- Multicast, 68
- multiple classes, 176
- multiple CPUs, 16, 73
- multiple-cnames option, 104
- MX record, 148, 151, 180

- name authority pointer record, 148
- name server, 2
- name space, 1, 66, 93, 125, 148–150
- named command, 15, 180
- named-checkconf command, 25
- named-checkzone command, 26, 107, 108
- named-compilezone command, 26, 29
- named-xfer option, 98
- NAPTR record, 148
- ndc, 85, 179
- ndots, 50
- ndots lwres option, 93
- negated element, 77, 78
- negative answers, 104
- negative response, 108
- network interface list, 118
- network service access point record, 148
- nibble, 69
- nibble label, 68, 111
- no-such-domain (NXDOMAIN), 152
- NOERROR, 127
- non-ASCII domain names, 48, 51
- none (address match list), 83
- NOTAUTH, 64
- NOTIFY messages, 19, 55
- notify messages, 176
- notify option, 104
- notify-delay option, 124
- notify-source option, 116, 132
- notify-source-v6 option, 116, 132
- NS record, 3, 148
- NSAP record, 148
- NSEC, 35, 145
- NSEC record, 148
- nslookup command, 51
 - interactive, 52
- nsupdate command, 29, 32, 61, 179
- null logging destination, 87
- NXDOMAIN, 92, 102, 125, 128, 152
- NXT record, 149

- one-answer, *see* transfer-format option
- OpenSSL, 10
- operating systems, 7
- options
 - acache-cleaning-interval, 129
 - acache-enable, 129
 - additional-from-auth, 105
 - additional-from-cache, 105, 129
 - allow-notify, 109
 - allow-query, 110

- allow-query-cache, 110
- allow-query-cache-on, 110
- allow-query-on, 110
- allow-recursion, 110
- allow-recursion-on, 111
- allow-transfer, 111
- allow-update, 63, 111, 144, 169
- allow-update-forwarding, 111
- allow-v6-synthesis, 111
- also-notify, 113, 140
- alt-transfer-source, 115
- alt-transfer-source-v6, 116
- auth-nxdomain, 102
- avoid-v4-udp-ports, 116
- avoid-v6-udp-ports, 116
- blackhole, 111
- cache-file, 17, 98
- check-integrity, 107
- check-mx, 107
- check-mx-cname, 108
- check-names, 107, 140, 179
- check-sibling, 108
- check-srv-cname, 108
- check-wildcard, 107
- cleaning-interval, 118
- clients-per-query, 123
- coresize, 117
- datasize, 117
- deallocate-on-exit, 102
- dialup, 102
- directory, 98
- disable-algorithms, 101
- disable-empty-zone, 127
- dnssec-accept-expired, 107
- dnssec-enable, 106
- dnssec-lookaside, 101
- dnssec-must-be-secure, 102
- dnssec-validation, 107
- dual-stack-servers, 109
- dump-file, 99
- edns-udp-size, 123, 131
- empty-contact, 127
- empty-server, 126
- empty-zones-enable, 127
- fake-iquery, 103
- fetch-glue, 103
- files, 117
- flush-zones-on-shutdown, 103
- forward, 109, 141
- forwarders, 71, 109, 142
- has-old-clients, 103
- heartbeat-interval, 102, 118
- host-statistics, 103
- host-statistics-max, 117
- hostname, 124
- interface-interval, 118
- ixfr-from-differences, 106
- key-directory, 98
- lame-ttl, 122
- listen-on, 111
- listen-on-v6, 112
- maintain-ixfr-base, 103
- masterfile-format, 123
- match-mapped-addresses, 106
- max-acache-size, 5, 129
- max-cache-size, 5, 118
- max-cache-ttl, 122
- max-clients-per-query, 123
- max-ixfr-log-size, 117
- max-journal-size, 117
- max-ncache-ttl, 122
- max-refresh-time, 123
- max-retry-time, 123
- max-transfer-idle-in, 114
- max-transfer-idle-out, 114
- max-transfer-time-in, 114
- max-transfer-time-out, 114
- max-udp-size, 123, 131
- memstatistics-file, 99
- min-refresh-time, 123
- min-retry-time, 123
- min-roots, 122
- minimal-responses, 103
- multi-master, 106
- multiple-cnames, 104
- named-xfer, 98
- notify, 104
- notify-delay, 124
- notify-source, 116, 132
- notify-source-v6, 116, 132

- pid-file, 99
- port, 101
- preferred-glue, 101
- provide-ixfr, 130
- query-source, 132, 167
- query-source-v6, 132
- querylog, 107
- queryport-pool-ports, 113
- queryport-pool-updateinterval, 113
- random-device, 101
- recursing-file, 99
- recursion, 104
- recursive-clients, 118
- request-ixfr, 131
- rfc2308-type1, 104
- root-delegation-only, 101
- rrset-order, 121, 129, 153
- serial-queries, 114
- serial-query-rate, 114
- server-id, 125
- sig-validity-interval, 122
- sortlist, 120, 147
- stacksize, 117
- statistics-file, 99
- statistics-interval, 119
- stats-server, 10, 99
- stats-server-v6, 100
- tcp-clients, 118
- tcp-listen-queue, 118
- tkey-dhkey, 98
- tkey-domain, 98
- tkey-gssapi-credential, 98
- topology, 119
- transfer-format, 114, 131, 175
- transfer-source, 115
- transfer-source-v6, 115
- transfers-in, 115
- transfers-out, 115
- transfers-per-ns, 115
- treat-cr-as-space, 105
- try-tcp-refresh, 108
- update-check-ksk, 108
- use-alt-transfer-source, 116
- use-id-pool, 104
- use-ixfr, 105
- use-queryport-pool, 113
- version, 124
- zero-no-soa-ttl, 108
- zero-no-soa-ttl-cache, 108
- zone-statistics, 104, 143
- options statement, 97, 133
- origin, 37
- packet loss, 92
- pid-file option, 99
- port, 16, 43, 54, 73, 84, 111, 138, 140
 - random, 76
- port (lwres), 73
- port option, 101
- preferred-glue option, 101
- primary, 3
- primary master, 3
- print-category (logging), 89
- print-severity (logging), 89
- print-time (logging), 89
- privileged, 74
- protocol, 147
- provide-ixfr option, 130
- PTR record, 149, 152
- pubkey (zone), 142
- PX record, 149
- query IDs, 104
- query logging, 20, 107
- query other name servers, 113
- query port pools, 113
- query-source option, 132, 167
- query-source-v6 option, 132
- querylog, 92
- querylog option, 107
- queryport, 113
- queryport-pool-ports option, 113
- queryport-pool-updateinterval option, 113
- quotes, 177
- random-device option, 101
- raw format zone file, 156
- RDATA, 147, 150
- record ordering, 121
- recursing-file option, 99

- recursion, 4, 110
- recursion desired (RD) bit, 45, 50
- Recursion Desired (RD) flag, 92
- recursion option, 104
- recursive lookups, 3
 - maximum, 118
- recursive name server, 3
- recursive queries, 110, 111
- recursive-clients option, 118
- Red Hat Linux, 11
- red-black-tree database, 141
- refresh queries, 176
- relative domain name, 93
- reload configuration, 17, 20
- remote name daemon control, *see* rndc
 - command
- removing expired resource records, 118
- request-ixfr option, 131
- resolv.conf, 60
- resolver, 1, 3
- resource data, 147
- resource limits, 117
- resource record, 2, 150
 - classes, 149
 - glue, 103
 - type, 147
- resource records set (RRset), 119
- reverse lookups, 43
- reverse mapping, 80
- reverse name resolution, 152
- reverse name space, 125, 149
- RFC, 183–186
- RFC 1034, 173
- RFC 1035, 173
- RFC 1918, 57
- RFC 920, 173
- rfc2308-type1 option, 104
- rndc, 179
- rndc command, 17, 21, 84
- rndc-confgen command, 21, 23
- rndc.conf, 21, 22
- rndc.key, 21
- root, 2, 21, 42, 66, 101, 106, 122, 125, 126, 139, 160
- root node, 1
- root-delegation-only option, 101
- round-robin, 121
- RP record, 149
- RPM, 11
- RR, *see* resource record
- RRset, 30
- rrset-order statement option, 121, 129, 153
- RRSIG, 35
- RRSIG record, 149
- RT record, 149
- search lwres option, 93
- search path elements, 93
- secondary, 3
- security, 166, 169
- semicolon, 79
- serial numbers, 152, 177
- serial-queries option, 114
- serial-query-rate option, 114
- server statement, 130
 - bogus, 130
 - edns, 131
 - edns-udp-size, 123, 131
 - keys, 131
 - max-udp-size, 123, 131
 - notify-source, 132
 - notify-source-v6, 132
 - provide-ixfr, 130
 - query-source, 132, 167
 - query-source-v6, 132
 - request-ixfr, 131
 - transfer-format, 114, 131
 - transfer-source, 115
 - transfer-source-v6, 115
 - transfers, 131
- server-id option, 125
- setuid, 16, 74, 169
- severity (logging), 88
- shared secret, 61
- sibling glue, 108
- SIG record, 149
- SIG(0), 64, 144
- sig-validity-interval option, 122
- SIGHUP, 17
- SIGINT, 17

- signals, 17
- signing a zone, 66
- SIGTERM, 17, 103
- size (logging), 88
- slave, 3, 152
- slave (zone type), 138
- slave servers, 3
- SOA record, 149, 152
- sortlist statement option, 120, 147
- source, 8
- split DNS, 57
- spoofing, 157
- SRV record, 149
- stacksize option, 117
- start of a zone of authority, 149
- statement
 - acl, 83
 - controls, 22, 23, 84
 - include, 85
 - key, 23, 86
 - logging, 87, 176
 - lwres, 93
 - masters, 93
 - options, 97
 - rrset-order, 121, 129, 153
 - sortlist, 120, 147
 - topology, 119
- statistics, 20, 119
- statistics dump, 127
- statistics file, 127
- statistics-file option, 99
- statistics-interval option, 119
- stats-server option, 10, 99
- stats-server-v6 option, 100
- stealth secondary zone, 163
- stealth server, 3
- stopping the server, 17, 19, 21
- stub (zone type), 138
- stub resolvers, 3
- stub zones, 181
- subdomain, 1, 2
- syslog, 89
- syslog logging destination, 88
- tcp-clients option, 118
- tcp-listen-queue option, 118
- text record, 149
- threads, 16, 73
- time-to-live, 4, 147, 152, 154
- TKEY, 64, 144
- TKEY exchange, 98
- tkey-dhkey option, 98
- tkey-domain option, 98
- tkey-gssapi-credential option, 98
- TLD, 101
- top level, 3
- top level domain, 1, *see* TLD
- topology option statement, 119
- Transaction Signatures, *see* TSIG
- transaction signatures, 169
- transfer-format option, 114, 131, 175
- transfer-source option, 115
- transfer-source-v6 option, 115
- transfers option (server), 131
- transfers-in option, 115
- transfers-out option, 115
- transfers-per-ns option, 115
- treat-cr-as-space option, 105
- trusted-keys statement, 132
- try-tcp-refresh option, 108
- TSIG, 61, 144, 169
- TSIG errors, 63
- TTL, 4, 147, 150, 152, 154
- TXT record, 149, 177
- type (zone), 138
- UDP message buffer size, 47
- umask, 181
- Unicast, 68
- University of California at Berkeley, 173
- unix controls channel, 84
- UNIX domain socket, 84, 179
- update-check-ksk option, 108
- update-policy (zone), 144
- upwards referral, 106
- use-alt-transfer-source option, 116
- use-id-pool option, 104
- use-ixfr option, 105
- use-queryport-pool option, 113
- version option, 124

- versions (logging), 87
- view lwres statement, 93
- view statement, 133
 - match-clients, 133
 - match-destinations, 133
 - match-recursive-only, 133
- Vixie, Paul, 173, 174, 183, 185, 186
- well known network services record, 149
- wildcard record, 58
- wildcards
 - non-terminal, 28, 107
- Windows, Microsoft, 7, 115
- WKS record, 149
- X.25, 149
- X.400, 149
- X25 record, 149
- zero-no-soa-ttl option, 108
- zero-no-soa-ttl-cache option, 108
- zone, 1, 2
 - frozen, 19
 - reload, 20
- zone file, 3
 - binary format, 156
 - formats, 156
 - raw format, 156
- zone integrity checks, 27, 107
- zone maintenance tasks, 118
- zone statement, 134
 - allow-notify, 109
 - allow-query, 110
 - allow-query-on, 110
 - allow-transfer, 111
 - allow-update, 111, 144, 169
 - allow-update-forwarding, 111
 - also-notify, 113, 140
 - alt-transfer-source, 115
 - alt-transfer-source-v6, 116
 - check-integrity, 107
 - check-mx, 107
 - check-mx-cname, 108
 - check-names, 140
 - check-sibling, 108
 - check-srv-cname, 108
 - check-wildcard, 107
 - database, 141
 - delegation-only, 141
 - dialup, 102
 - file, 138
 - forward, 141
 - forwarders, 142
 - ixfr-base, 142
 - ixfr-from-differences, 106
 - ixfr-tmp-file, 142
 - journal, 142
 - key-directory, 98
 - maintain-ixfr-base, 103
 - masterfile-format, 123
 - masters, 93
 - max-ixfr-log-size, 117
 - max-journal-size, 117
 - max-refresh-time, 123
 - max-retry-time, 123
 - max-transfer-idle-in, 114
 - max-transfer-idle-out, 114
 - max-transfer-time-in, 114
 - max-transfer-time-out, 114
 - min-refresh-time, 123
 - min-retry-time, 123
 - multi-master, 106
 - notify, 104
 - notify-delay, 124
 - notify-source, 132
 - notify-source-v6, 132
 - pubkey, 142
 - sig-validity-interval, 122
 - transfer-source, 115
 - transfer-source-v6, 115
 - try-tcp-refresh, 108
 - type, 138
 - update-check-ksk, 108
 - update-policy, 144
 - use-alt-transfer-source, 116
 - zero-no-soa-ttl, 108
 - zone-statistics, 143
- zone transfer methods, 131
- zone transfers, 3
 - full, 57

- incremental, 56
- maximum, 115
- non-incremental, 106
- options, 113
- zone-statistics option, 104, 143
- zones, built-in, 124